



9x19 Luger FMJ 7,5 g / 115 gr

CIP-approved round.

Reliable in extreme environmental conditions.

Preserves the weapon's service life.

Application:

Excellent choice for home defense and for law enforcement with its low lead exposure. Ideal for indoor training.

All components are produced to perform seamlessly together for perfect functioning in all common types of weapons.

Cartridge:	
Projectile	FMJ, 7,5 g / 115 gr
Projectile material	CuZn alloy jacket with lead core
Primer / propellant	Standard / Double base powder
Case material	CuZn alloy
MFS article number	2426476

Performance:

Term of reference	C.I.P.
Temperature range	-20°C to +52°C
Mean case mouth pressure (bar)	max. 2350
Muzzle velocity (m/s)	375
Muzzle energy (J)	527
Accuracy	D100% ≤ 80mm at 25m

Packaging:

50 rds./cardboard box, 1 000 rds./cardboard box

Images, drawings, technical details and in particular head stamps are for illustration purpose only, which do not necessarily correspond to actual products.

All information and specifications shown in this data card are non-binding and subject to alterations without prior notice at any time.

version 30. June 2023



Postal address: Po. Box 9 Sirok, Hungary HU-3332 Phone: +36 36 561 300 / E-mail: info@mfsdefense.com

www.mfs-ammunition.com