

# 38 Special



## LIST OF COMPONENTS



<b>Bullet</b>	Type	JHP
	Weight	10,2 g / 158 gr
	Material	CuZn10 / Gilding metal with lead core

<b>Case</b>	Material	CuZn30 / Brass
-------------	----------	----------------

<b>Primer</b>	Boxer
---------------	-------

<b>Propellant</b>	Single or Double base powder
-------------------	------------------------------

## PRODUCT



<b>Cartridge</b>	Weight	14,8 g / 228 gr
	Max. length	39,3 mm / 1,5 inch

## PACKAGING



<b>Inner</b>	Material	Cardboard box with plastic tray
	Quantity	50 rds

<b>Outer</b>	Material	Cardboard box
	Quantity	1.000 rds
	Weight	~16,1 kg

## PERFORMANCE



<b>Operation temperature range:</b>	-20°C to +52°C
-------------------------------------	----------------

<b>Mean pressure:</b>	max. 1500 bar / 150 MPa
-----------------------	-------------------------

C.I.P. PK pressure:	max. 1725 bar / 173 MPa
---------------------	-------------------------

<b>Muzzle velocity:</b>	270 m/s ± 10 m/s (886 fps)
-------------------------	----------------------------

Test barrel:	150 mm (5,9 inch)
--------------	-------------------

Distance:	5 m (16,4 ft)
-----------	---------------

Standard deviation:	max. 12 m/s (40 fps)
---------------------	----------------------

<b>Precision:</b>	D100% ≤ 80mm
-------------------	--------------

Distance:	25 m (82 ft)
-----------	--------------

<b>Bullet extraction force:</b>	Min.: 200 N / 45 lbs
---------------------------------	----------------------

<b>Properties:</b>	Ballistic, technical properties is according to C.I.P.
--------------------	--

Images, drawings, technical details and in particular head stamps are for illustration purpose only, which do not necessarily correspond to actual products.

