

45 AUTO



LIST OF COMPONENTS

| | | |
|---------------|----------|---------------------------------------|
| Bullet | Type | JHP |
| | Weight | 14,9 g / 230 gr |
| | Material | CuZn10 / Gilding metal with lead core |

| | | |
|-------------|----------|----------------|
| Case | Material | CuZn30 / Brass |
|-------------|----------|----------------|

| | |
|---------------|-------|
| Primer | Boxer |
|---------------|-------|

| | |
|-------------------|------------------------------|
| Propellant | Single or Double base powder |
|-------------------|------------------------------|

PRODUCT

| | | |
|------------------|-------------|--------------------|
| Cartridge | Weight | 20,7 g / 320 gr |
| | Max. length | 30,8 mm / 1,2 inch |

PACKAGING

| | | |
|--------------|----------|---------------------------------|
| Inner | Material | Cardboard box with plastic tray |
| | Quantity | 50 rds |

| | | |
|--------------|----------|---------------|
| Outer | Material | Cardboard box |
| | Quantity | 1.000 rds |
| | Weight | ~22,5 kg |

PERFORMANCE

Operation temperature range: -20°C to +52°C

Mean pressure: max. 1.300 bar / 130 MPa

C.I.P. PK pressure: max. 1.495 bar / 149 MPa

Muzzle velocity: 260 m/s ± 10 m/s (853 fps)

Test barrel: 150 mm (5,9 inch)

Distance: 5 m (16,4 ft)

Standard deviation: max. 12 m/s (40 fps)

Precision: D100% ≤ 60mm

Distance: 25 m (82 ft)

Bullet extraction force: Min.: 200 N / 45 lbs

Properties: Ballistic, technical properties is according to C.I.P.

Images, drawings, technical details and in particular head stamps are for illustration purpose only, which do not necessarily correspond to actual products.