



5,56x45 SS109

4 g / 63 gr

NATO standard steel core service ammunition. It provides a high accuracy. Excellent reliability wherever the mission may take place. Cost effective versatile round. Trusted by armed forces worldwide. Reliable in extreme environmental conditions.

Application:

Excellent choice for training and service. One of the world most preferred military ammunition.

All components are produced to perform seamlessly together for perfect functioning in all common types of weapons.

Performance:

Term of reference	MCMOPI
Temperature range	-20°C to +52°C
Mean case mouth pressure (bar)	max. 4300
Muzzle velocity (m/s)	945
Muzzle energy (J)	1786
Accuracy	D100% ≤ 120mm at 300m

Cartridge:

Projectile	SS109, 4 g / 63 gr
Projectile material	CuZn alloy jacket with steel core
Primer / propellant	Standard / Double base powder
Case material	CuZn alloy
Article number	Tbd.

Packaging:

50 rds./cardboard box, 1 000 rds./cardboard box

Technical specification and numerical data are given as an indication only and are of no contractual nature. version 30. Aug. 2021



RUAG Hungarian Ammotec Inc

Address: Belső gyártelep 1002/35. hrsz., H-3332 Sirok, Hungary

Postal address: Po. Box 9 Sirok, Hungary HU-3332

Phone: +36 36 561 300 / E-mail: info@mfsammunition.com

www.mfs-ammunition.com