



9x19 Luger FMJ-FP

10 g / 154 gr

*CIP-approved round minimizes exposure to lead.
Reliable in extreme environmental conditions.
Preserves the weapon's service life. Low lead
exposure. Extrem high stopping power.*

Application:

Excellent choice for home defense and law enforcement .

All components are produced to perform seamlessly together for perfect functioning in all common types of weapons.

Performance:

Term of reference	C.I.P.
Temperature range	-20°C to +52°C
Mean case mouth pressure (bar)	max. 2350
Muzzle velocity (m/s)	290
Muzzle energy (J)	421
Accuracy	D100% ≤ 80mm at 25m

Cartridge:

Projectile	FMJ-FP, 10 g / 154 gr
Projectile material	CuZn alloy jacket with lead core
Primer / propellant	Standard / Double base powder
Case material	CuZn alloy
MFS article number	2426478

Packaging:

50 rds./cardboard box, 1 000 rds./cardboard box

Images, drawings, technical details and in particular head stamps are for illustration purpose only, which do not necessarily correspond to actual products.

All information and specifications shown in this data card are non-binding and subject to alterations without prior notice at any time.

version 30. June 2023



MFS Defense Zrt.

Address: Belső gyártelep 1002/35. hrsz., H-3332 Sirok, Hungary

Postal address: Po. Box 9 Sirok, Hungary HU-3332

Phone: +36 36 561 300 / E-mail: info@mfsdefense.com

www.mfs-ammunition.com