

38 SUPER AUTO



LIST OF COMPONENTS



Bullet	Type	FMJ
	Weight	8,0 g / 124 gr
	Material	CuZn10 / Gilding metal with lead core

Case	Material	CuZn30 / Brass
-------------	----------	----------------

Primer	Boxer
---------------	-------

Propellant	Single or Double base powder
-------------------	------------------------------

PRODUCT



Cartridge	Weight	12,8 g / 198 gr
	Max. length	32,45 mm / 1,3 inch


PACKAGING



Inner	Material	Cardboard box with plastic tray
	Quantity	50 rds

Outer	Material	Cardboard box
	Quantity	800 rds
	Weight	~10,8 kg

PERFORMANCE



Operation temperature range: -20°C to +52°C

Mean pressure: max. 2.300 bar / 230 Mpa

C.I.P. PK pressure: max. 2.645 bar / 265 Mpa

Muzzle velocity: 430 m/s ± 10 m/s (1.410 fps)

Test barrel: 150 mm (5,9 inch)

Distance: 5 m (16,4 ft)

Standard deviation: max. 12 m/s (40 fps)

Precision: D100% ≤ 80mm

Distance: 25 m / 27,3 yd

Bullet extraction force: Min.: 200 N / 45 lbs

Properties: Ballistic, technical properties is according to C.I.P.

Images, drawings, technical details and in particular head stamps are for illustration purpose only, which do not necessarily correspond to actual products.

