

38 Special



LIST OF COMPONENTS

Bullet	Type	FMJ-FP
	Weight	10,2 g / 158 gr
	Material	CuZn10 / Gilding metal with lead core

Case	Material	CuZn30 / Brass
-------------	----------	----------------

Primer	Boxer
---------------	-------

Propellant	Single or Double base powder
-------------------	------------------------------

PRODUCT

Cartridge	Weight	14,8 g / 228 gr
	Max. length	38,5 mm / 1,5 inch

PACKAGING

Inner	Material	Cardboard box with plastic tray
	Quantity	50 rds

Outer	Material	Cardboard box
	Quantity	1.000 rds
	Weight	~16,1 kg

PERFORMANCE

Operation temperature range: -20°C to +52°C

Mean pressure: max. 1500 bar / 150 MPa

C.I.P. PK pressure: max. 1725 bar / 173 MPa

Muzzle velocity: 270 m/s ± 10 m/s (886 fps)

Test barrel: 150 mm (5,9 inch)

Distance: 5 m (16,4 ft)

Standard deviation: max. 12 m/s (40 fps)

Precision: D100% ≤ 80mm

Distance: 25 m (82 ft)

Bullet extraction force: Min.: 200 N / 45 lbs

Properties: Ballistic, technical properties is according to C.I.P.

Images, drawings, technical details and in particular head stamps are for illustration purpose only, which do not necessarily correspond to actual products.