

7,62x39



LIST OF COMPONENTS



Bullet	Type	FMJ
	Weight	8,0 g / 124 gr
	Material	CuZn10 / Gilding metal with lead core

Case	Material	CuZn30 / Brass
-------------	----------	----------------

Primer	Boxer
---------------	-------

Propellant	Single or Double base powder
-------------------	------------------------------

PRODUCT



Cartridge	Weight	17,7 g / 273 gr
	Max. length	56,00 mm / 2,2 inch

PACKAGING



Inner	Material	Cardboard box
	Quantity	50 rds

Outer	Material	Cardboard box
	Quantity	1.000 rds
	Weight	~18,2 kg

PERFORMANCE



Operation temperature range:	-20°C to +52°C
-------------------------------------	----------------

Mean pressure:	max. 3.550 bar / 355 MPa
-----------------------	--------------------------

C.I.P. PK pressure:	max. 4.085 bar / 408 MPa
---------------------	--------------------------

Muzzle velocity:	740 m/s ±10 m/s (2428 fps)
-------------------------	----------------------------

Test barrel:	600 mm (23,6 inch)
--------------	--------------------

Distance:	5 m (16,4 ft)
-----------	---------------

Standard deviation:	max. 15 m/s (49 fps)
---------------------	----------------------

Precision:	R50% ≤ 60mm
-------------------	-------------

Distance:	100 m (328,1 ft)
-----------	------------------

Bullet extraction force:	Min.: 200 N / 45 lbs
---------------------------------	----------------------

Properties:	Ballistic, technical properties is according to C.I.P.
--------------------	--

Images, drawings, technical details and in particular head stamps are for illustration purpose only, which do not necessarily correspond to actual products.

