

223 Remington



LIST OF COMPONENTS



Bullet	Type	FMJ-BT
	Weight	3,56 g / 55 gr
	Material	CuZn10 / Gilding metal with lead core

Case	Material	CuZn30 / Brass
------	----------	----------------

Primer	Boxer
--------	-------

Propellant	Single or Double base powder
------------	------------------------------

PRODUCT



Cartridge	Weight	11,7 g / 180 gr
	Max. length	56,4 mm / 2,2 inch

PACKAGING



Inner	Material	Cardboard box
	Quantity	50 rds

Outer	Material	Cardboard box
	Quantity	1.000 rds
	Weight	~12,3 kg

PERFORMANCE



Operation temperature range:	-20°C to +52°C
------------------------------	----------------

Mean pressure:	max. 4300 bar / 430 MPa
----------------	-------------------------

C.I.P. PK pressure:	max. 4945 bar / 495 MPa
---------------------	-------------------------

Velocity:	1010 m/s $\pm$ 7 m/s (3313 fps)
-----------	---------------------------------

Test barrel:	600 mm (23,6 inch)
--------------	--------------------

Distance:	5 m (16,4 ft)
-----------	---------------

Standard deviation:	max. 8 m/s (26 fps)
---------------------	---------------------

Precision:	D100 % $\leq$ 65 mm
------------	---------------------

Distance:	100 m (328 ft)
-----------	----------------

Bullet extraction force:	Min.: 200 N / 45 lbs
--------------------------	----------------------

Properties:	Ballistic, dimensional and marking properties: according to C.I.P.
-------------	--

